



# IS-B-335/460/650 Selective Stand-alone Soldering Systems

The InterSelect 335, 460 und 650 stand-alone selective soldering systems are designed to meet the needs of lean manufacturing in combination with flexibility and throughput at minimal cost.

IS-B-335S, IS-B-460S/D/P and IS-B-650S/P selective soldering systems are completely automated "stand-alone systems" with a unique manual hand loaded sliding system, able to handle boards up to 650x650mm (25.6°x25.6°).

The most economic machine, the IS-B-335 needs just 1 sqm of space.

All soldering units are equipped with our inert hot nitrogen atmosphere for better soldering results and to assist the prevention of oxidation. Each solder pot comes with this inert atmosphere feature. As well as all machines come with a micro jet fluxer system for clean soldering results and very low flux consumption. All machines can be equipped with a unique large top and bottom side preheating system, controlled by a pyrometer. All process parameters are ready for data transfer.



## The best machine in its class, with unique features

#### **Unique Features**

The large soldering area can handle almost every board	IS-B-335: 335 x 335 mm IS-B-460: 460 x 460 mm IS-B-650: 650 x 650 mm
Smallest footprints in its class	IS-B-335: just 1 m <sup>2</sup> IS-B-460: just 1,45 m <sup>2</sup> IS-B-650: just 2,25 m <sup>2</sup>
Large adjustable, energy-efficient top and bottom preheaters (heater size matches PCB size)	IS-B-335: adjustable 1,5 to 4,5 kW per side IS-B-460: adjustable 1,5 to 6 kW per side IS-B-650: adjustable 1,5 to 7,5 kW per side
Optional	Standard Features
Automatic laser wave height control an correction	Integrated PC with Windows 7 features the user-friendly software
Laser pyrometer control with profiling	Network-comapatible remote maintenance

# This stand-alone selective concept covers six basic machines:



Multi wave for extremely fast cycle times

Create soldering program while the machine is running with the

optional IS Photoscan offline programming software

#### IS-B-335S

- 1 x Solder pot
- 1 x Micro Drop Fluxer



Mini wave for solder joints with close components

7° and 0° axis system enable use of wetable and jet nozzles


#### IS-B-460D

- $2\ x$  Solder pots for different alloys
- 1 x Micro Drop Fluxer



# IS-B-460S

- $1 \times Solder pot$
- 1 x Micro Drop Fluxer



#### IS-B-460P

- 2 x Solder pots for double speed
- 2 x Micro Drop Fluxer for double speed
- 50% cycle time



## IS-B-650S

- 1 x Solder pot
- 1 x Micro Drop Fluxer



## IS-B-650P

- 2 x Solder pots for double speed
- 2 x Micro Drop Fluxer for double speed
- 50% cycle time